

PRODUCTS /BARREL SHAPE BLOCK TYPE BBFE



Load capacity: from 1t to 35 t

Hooks: DIN 15401/DIN15402 or shank hook

rotating on axial bearing

Weight: in steel or cast iron according to customer needs.

Storage: a support is needed to place the block

Certification: in order to guarantee their quality O.F.S. products can be certified upon request according to the International Standards by

the main certification bodies

Design: blocks are produced according to O.F.S. design or developed on customer's specification.

PRODUCTS /BARREL SHAPE BLOCK TYPE BMG



Load capacity: from 2t to 15 t

Hooks: DIN 15401/DIN15402 or shank hook rotating on swivel.


Weight: in cast iron

Storage: a support is needed to place the block

Certification: in order to guarantee their quality O.F.S. products can be certified upon request according to the International Standards by

the main certification bodies

Design or developed on customer's specification.



| | Load capacity (t) | øRope (mm) | Weight (kg) | |
|-----------|-------------------|------------|-------------|-----------|
| BMG - 2 | 2 | 13 | 16 | BFG - 2 |
| BMG - 3 | 3 | 16 | 28 | BFG - 3 |
| BMG - 5 | 5 | 19 | 49 | BFG - 5 |
| BMG - 7.5 | 7.5 | 22 | 76 | BFG - 7.5 |
| BMG - 10 | 10 | 26 | 130 | BFG - 10 |
| BMG - 15 | 15 | 32-35 | 190 | BFG - 15 |
| BMG - 20 | 20 | 39-42 | 260 | BFG - 20 |
| BMG - 25 | 25 | 43-48 | 280 | BFG - 25 |